



ADVANTAGES

- Starter box with hour counter, emergency stop and 2 electrical sockets on front panel.
- Liquid-cooled, 4-stroke, twin-cylinder diesel engine with electric starter and 12V battery.
- Piston compressor with pneumatic control, interstage cooler and aftercooler for improved air quality and excellent cooling.
- Generator fitted with 30mA residual current protection.
- Epoxy-painted CE air tank fitted with all safety features: glycerine bath pressure gauge, safety valve, non-return valve, condensate drain and 2 VL and HGV air outlet reels with double-safety quick-release couplings connected to 1 filter, pressure reducer and lubricator.
- Supplied with 1 x 1.50 metre exhaust hose and 1 x floor passage.

FEATURES

MOTOR TYPE	KOHLER KDW702 (686 cm ³)
ENGINE POWER	11,7 kW - 16 hp
FUEL TANK CAPACITY	23 L deported
FUEL CONSUMPTION	4 L/h à 2800 rpm
NO. OF CYLINDERS / STAGES	2 (727 cm ³) / 2
COMPRESSOR ROTATION SPEED	1000 rpm
FLOW RATE	56 m ³ /h - 933 L/min
MAX. PRESSURE	12 BAR
GENERATOR TYPE	10 kVA (8 kW) / 400V (3ph)
SOCKET OUTLET	1 single-phase 16A + 1 three-phase 16A
AIR TANK	120 L
AIR OUTLET	2 reels 20 m (LV + HGV)
SOUND LEVEL	92 dB(A) at 1 meter
DIMENSIONS *	L. 1100 x W. 1246 x H. 1710 mm
NET WEIGHT *	380 kg

* Weights and dimensions are given for information only and may change at any time.

OPTIONS

- EE** Electrical reel 3G1.5 mm² 230V - 15 m
- KRN** Quick-connect kit for fuel jerrycan
- DD** Starter box offset by 2 metres
- PA** Automatic condensate drain



Contact us

Please contact us for information.

By mail contact@guernet.com • By phone +33 (0)3.45.88.30.30

Address 51 Route de Montargis - 89300 Joigny (FRANCE)