



ADVANTAGES

- Liquid-cooled, 4-stroke, twin-cylinder diesel engine with electric starter and 12V battery.
- Piston compressor with pneumatic regulation, interstage cooler and aftercooler for improved air quality and excellent cooling.
- Epoxy-painted CE air tank with full safety features: glycerine pressure gauge, safety valve, non-return valve, automatic condensate drain.
- 2 LV and HGV air reels with double-safety quick-release couplers connected to 1 lubricating filter regulator.

FEATURES

MOTOR TYPE	KOHLER KDW702 (686 cm ³) - 11.7 kW	GENERATOR TYPE	7 kVA (5,6 kW) / 230V (1ph) - 400V (3ph)
FUEL CAPACITY	23 L	SOCKET OUTLET	1 x 230V 16 A
FUEL CONSUMPTION	4 L/h 2800 rpm	AIR TANK	120 L
NO. OF CYLINDERS / STAGES	2 (727 cm ³) / 2	AIR OUTLET	1x LV 20 m + 1x HGV 20 m
COMPRESSOR SPEED	1000 rpm	NOISE LEVEL	87 dB(A) at 1 meter
FREE AIR DELIVERY	42 m ³ /h - 700 L/min	DIMENSIONS (folded machine)	L. 1711 x W. 1115 x H. 1693 mm
MAX PRESSURE	12 BAR	NET WEIGHT	800 kg

STANDARD ACCESSORIES

- 1 Exhaust hose Ø32mm lg 50cm
- 1 Exhaust pipe Ø32mm
- 1 Ø160 angled combination funnel



OPTIONS

DD	Offset starter box	KRN	Quick-connect kit for fuel jerrycan
EE	Electrical reel 3G1.5 mm ² - 15 m		

Contact us

Please contact us for information.
 By mail contact@guernet.com • By phone +33 (0)3.45.88.30.30
 Address 51 Route de Montargis - 89300 Joigny (FRANCE)



Non-contractual illustration

ADVANTAGES

- Hydraulic self-centring wheel lock chuck.
- Chuck rotation by electric motor.
- Wired control panel.
- Limit switches for safe machine folding.

FEATURES

VOLTAGE / FREQUENCY	400 V three-phase / 50 Hz
MOTOR POWER CHUCK	1,1 kW
OPERATING VOLTAGE	24 V
CHUCK ROTATION SPEED	6 rpm
FORCE MAX. BEAD BREAKER	25000 N
Ø - RIM	13 - 26"

Ø - WHEEL	1380 mm max
MAX. WIDTH - WHEEL	600 mm
MAX. WEIGHT - WHEEL	500 kg
MAX. TRAVEL TROLLEY	625 mm
HEIGHT VAN FLOOR / GROUND	max. 650 mm
WORKING HEIGHT CHUCK / FLOOR	min. 445 mm / max. 700 mm

STANDARD ACCESSORIES

- 2 levers, 1 heel clamp, 1 3rd hand tool, 1 grease gun, grease brush, 1 funnel.



OPTIONS

MAAP886259	4 protection rings for ALU rims
MAAP888168	LV set (except ALU rims)
MAAP20169081	Bead breaker disc
MAAP20169082	Bead breaker disc + spout

MAAPWIRELESS	Wireless kit for control panel
EQUI-BOXB160	On-board wheel balancer
MAAP3M2762	Kit for 17.5' HGV wheel for B160
MAAP886259A	Ring for 22.5' ALU rim

Contact us

Please contact us for information.

By mail contact@guernet.com • By phone +33 (0)3.45.88.30.30

Address 51 Route de Montargis - 89300 Joigny (FRANCE)